

COLOURED FACING TISSUES,
Insulation Tissues



Metric

Typical Product Codes Supplied	P500PVB		
Nominal Thickness	0.50mm		
Binder	UF/PVA		
Comments	Black Painted		
	P500PVB	Made to order Minimum	Made to order Maximum
Glass Type	C-glass	-	-
Fibre Diameter	12-13µ	-	-
Weight	60-65 g/m ²	-	-
Nominal Thickness	0.60 mm	0.2 mm	1.1 mm
Binder Type	UF/PVA	-	-
Binder Content	24%	-	-
Fire Rating to AS 1530, Part 3-1982 Ignitability Index	0 (Range 0-20)	-	-
Spread of Flame Index	0 (Range 0-10)	-	-
Heat Evolved Index	0 (Range 0-10)	-	-
Smoke Developed Index	2 (Range 0-10)	-	-
Roll Width	-	-	1.7 m
Roll Length	400 m	-	500 m

Imperial

Typical Product Codes Supplied	P500PVB		
Nominal Thickness	0.020 in.		
Binder	UF/PVA		
Comments	Black Painted		
	P500PVB	Made to order Minimum	Made to order Maximum
GGlass Type	C-glass	-	-
Fibre Diameter	0.0005 in.	-	-
Weight	0.205 oz/ft. ²	-	-
Nominal Thickness	0.024 in.	0.008 in.	0.043 in.
Binder Type	UF/PVA	-	-
Binder Content	24%	-	-
Fire Rating to AS 1530, Part 3-1982 Ignitability Index	0 (Range 0-20)	-	-
Spread of Flame Index	0 (Range 0-10)	-	-
Heat Evolved Index	0 (Range 0-10)	-	-
Smoke Developed Index	2 (Range 0-10)	-	-
Roll Width	-	-	67 in.
Roll Length	1300 ft.	-	1650 ft.